

**SAFETY DATA SHEET**  
SOL-X ALUMINIUM ANTI-SEIZE

Page 1  
Issued: 09/01/08  
Revision No: 4

**1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING**

**Product name:** SOL-X ALUMINIUM ANTI-SEIZE  
**Product code:** FN 0710  
**Company name:** Central Solutions (GB) Ltd  
Unit 59 Askern Industrial Estate  
Moss Road  
Askern  
Doncaster  
DN6 ODD  
Tel: +44(0)7775 514020  
Fax: +44(0)1302 708895

**2. COMPOSITION / INFORMATION ON INGREDIENTS**

**Hazardous ingredients:** LOW BOILING POINT MODIFIED NAPHTHA-NAPHTHA(PETROLEUM) SOLVENT REFINED LIGHT 30-50%  
EINECS: 265-086-6 CAS: 64741-84-0  
[F] R11; [Xi] R38; [N] R51/53; [Xn] R65; [-] R67

- PROPANE 1-10%  
EINECS: 200-827-9 CAS: 74-98-6  
[F+] R12
- ISOBUTANE 1-10%  
EINECS: 200-857-2 CAS: 75-28-5  
[F+] R12
- BUTANE 10-30%  
EINECS: 203-448-7 CAS: 106-97-8  
[F+] R12

**3. HAZARDS IDENTIFICATION**

**Main hazards:** Extremely flammable. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**4. FIRST AID MEASURES (SYMPTOMS)**

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

[cont...]

## SAFETY DATA SHEET

SOL-X ALUMINIUM ANTI-SEIZE

### 4. FIRST AID MEASURES (ACTION)

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.
- Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.
- Ingestion:** Wash out mouth with water. Consult a doctor.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 5. FIRE-FIGHTING MEASURES

- Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.
- Exposure hazards:** In combustion emits toxic fumes.
- Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

### 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.
- Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.
- Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 7. HANDLING AND STORAGE

- Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.
- Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Hazardous ingredients:** PROPANE  
WEL (8 hr exposure limit): 1800 mg/m<sup>3</sup> WEL (15 min exposure limit): 7200 mg/m<sup>3</sup>
- ISOBUTANE  
WEL (8 hr exposure limit): 2400 mg/m<sup>3</sup> WEL (15 min exposure limit): 9600 mg/m<sup>3</sup>
  - BUTANE  
WEL (8 hr exposure limit): 1450 mg/m<sup>3</sup> WEL (15 min exposure limit): 1810 mg/m<sup>3</sup>
- Engineering measures:** Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.
- Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Protective gloves.  
**Eye protection:** Safety glasses. Ensure eye bath is to hand.  
**Skin protection:** Protective clothing.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**State:** Aerosol  
**Colour:** Grey  
**Odour:** Characteristic odour  
**Evaporation rate:** Fast  
**Oxidising:** Non-oxidising (by EC criteria)  
**Solubility in water:** Insoluble  
**Flash point°C:** -34

**10. STABILITY AND REACTIVITY**

**Stability:** Stable under normal conditions.  
**Conditions to avoid:** Heat.  
**Materials to avoid:** Strong oxidising agents. Strong acids.  
**Haz. decomp. products:** In combustion emits toxic fumes.

**11. TOXICOLOGICAL INFORMATION**

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

**12. ECOLOGICAL INFORMATION**

**Mobility:** Readily absorbed into soil.  
**Persistence and degradability:** Not biodegradable.  
**Bioaccumulative potential:** Bioaccumulation potential.  
**Other adverse effects:** Toxic to aquatic organisms. Toxic to soil organisms.

**13. DISPOSAL CONSIDERATIONS**

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**14. TRANSPORT INFORMATION****ADR / RID**

**UN no:** 1950 **ADR Class:** 2  
**Classification code:** 5F  
**Shipping name:** AEROSOLS  
**Labelling:** 2.1



**SAFETY DATA SHEET**  
SOL-X ALUMINIUM ANTI-SEIZE

**IMDG / IMO**

**UN no:** 1950 **Class:** 2  
**EmS:** F-D,S-U **Marine pollutant:** .  
**Labelling:** 2.1

**IATA / ICAO**

**UN no:** 1950 **Class:** 2  
**Labelling:** 2.1

**15. REGULATORY INFORMATION**

**Hazard symbols:** Extremely flammable.  
Irritant.  
Dangerous for the environment.



**Risk phrases:** R12: Extremely flammable.  
R38: Irritating to skin.  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R67: Vapours may cause drowsiness and dizziness.

**Safety phrases:** S16: Keep away from sources of ignition - No smoking.  
S23: Do not breathe ...  
S38: In case of insufficient ventilation, wear suitable respiratory equipment.  
S51: Use only in well-ventilated areas.  
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

**Precautionary phrases:** Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.  
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

**16. OTHER INFORMATION**

**Risk phrases used in s.2:** R11: Highly flammable.  
R38: Irritating to skin.  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

**SAFETY DATA SHEET**  
SOL-X ALUMINIUM ANTI-SEIZE

environment.

R65: Harmful: may cause lung damage if swallowed.

R67: Vapours may cause drowsiness and dizziness.

R12: Extremely flammable.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.