

SAFETY DATA SHEET

SOL-X BRAKE CLEANER

Page 1

Issued: 02/04/07

Revision No: 3

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: SOL-X BRAKE CLEANER
Company name: Central Solutions (GB) Ltd
Unit 59 Askern Industrial Estate
Moss Road
Askern
Doncaster
DN6 ODD
Tel: +44(0)7775 514020
Fax: +44(0)1302 708895

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: LOW BOILING POINT MODIFIED NAPHTHA-NAPHTHA(PETROLEUM) SOLVENT REFINED LIGHT 50-70%
EINECS: 265-086-6 CAS: 64741-84-0
[F] R11; [Xi] R38; [N] R51/53; [Xn] R65; [-] R67

- ACETONE 1-10%
EINECS: 200-662-2 CAS: 67-64-1
[F] R11; [Xi] R36; [Xi] R66; [-] R67
- PROPAN-2-OL 30-50%
EINECS: 200-661-7 CAS: 67-63-0
[F] R11; [Xi] R36; [-] R67

3. HAZARDS IDENTIFICATION

Main hazards: Extremely flammable. Irritating to eyes and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

[cont...]

SAFETY DATA SHEET

SOL-X BRAKE CLEANER

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: ACETONE

WEL (8 hr exposure limit): 1210 mg/m³ WEL (15 min exposure limit): 3620 mg/m³

- PROPAN-2-OL

WEL (8 hr exposure limit): 999 mg/m³ WEL (15 min exposure limit): 1250 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Aerosol

SAFETY DATA SHEET

SOL-X BRAKE CLEANER

Colour: Colourless**Odour:** Characteristic odour**Evaporation rate:** Fast**Oxidising:** Non-oxidising (by EC criteria)**Solubility in water:** Insoluble**Flash point°C:** -18**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions.**Conditions to avoid:** Heat.**Materials to avoid:** Strong oxidising agents. Strong acids.**Haz. decomp. products:** In combustion emits toxic fumes.**11. TOXICOLOGICAL INFORMATION****Hazardous ingredients:** ACETONE

IVN RAT LD50 5500 mg/kg

ORL MUS LD50 3 gm/kg

ORL RAT LD50 5800 mg/kg

• PROPAN-2-OL

IVN RAT LD50 1088 mg/kg

ORL MUS LD50 3600 mg/kg

ORL RAT LD50 5045 mg/kg

SCU MUS LDLO 6 gm/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.**12. ECOLOGICAL INFORMATION****Mobility:** Readily absorbed into soil.**Persistence and degradability:** Not biodegradable.**Bioaccumulative potential:** Bioaccumulation potential.**Other adverse effects:** Toxic to aquatic organisms. Toxic to soil organisms.**13. DISPOSAL CONSIDERATIONS****NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION****ADR / RID****UN no:** 1950**ADR Class:** 2**Classification code:** 5A**Shipping name:** AEROSOLS

SAFETY DATA SHEET

SOL-X BRAKE CLEANER

Labelling: 2.2



IMDG / IMO

UN no: 1950

Class: 2

EmS: F-D,S-U

Marine pollutant: .

Labelling: 2.2

IATA / ICAO

UN no: 1950

Class: 2

Labelling: 2.2

15. REGULATORY INFORMATION

Hazard symbols: Extremely flammable.

Irritant.

Dangerous for the environment.



Risk phrases: R12: Extremely flammable.

R36/38: Irritating to eyes and skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe spray.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

S51: Use only in well-ventilated areas.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to

SAFETY DATA SHEET

SOL-X BRAKE CLEANER

the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R11: Highly flammable.
R38: Irritating to skin.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65: Harmful: may cause lung damage if swallowed.
R67: Vapours may cause drowsiness and dizziness.
R36: Irritating to eyes.
R66: Repeated exposure may cause skin dryness or cracking.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.