

SOL-X EXTREME SYNTHETIC LUBE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : Sol-X EXTREME SYNTHETIC LUBE
 Product code : SXEXT500
 Type of product : Aerosol
 Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
 Industrial/Professional use spec : For professional use only
 Use of the substance/mixture : Lubricant for chains, wires and cables.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

CENTRAL SOLUTIONS (GB) LTD
 CENTRAL SOLUTIONS (GB) LTD
 UNITED KINGDOM
 Tel: 01302 708 895 Fax: +44 01302 708 895 Email: info@solxsolutions.com

1.4. Emergency telephone number

Emergency number : Mon to Fri 8.30am to 5.00pm - 01302 708 895

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] Mixture: SDS < 2015 : Show CLP information only

Aerosol 1 H222;H229
 Skin Irrit. 2 H315
 Aquatic Chronic 3 H412

Full text of H-phrases: see section 16

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Extra labelling to display Extra classification(s) to display

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) : Danger

Hazard statements (CLP) : H222 - Extremely flammable aerosol
 H229 - Pressurised container: May burst if heated
 H315 - Causes skin irritation
 H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (CLP) : P102 - Keep out of reach of children
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 P211 - Do not spray on an open flame or other ignition source
 P251 - Do not pierce or burn, even after use
 P264 - Wash hands thoroughly after handling
 P280 - Wear protective gloves
 P302+P352 - IF ON SKIN: Wash with plenty of soap, water
 P362+P364 - Take off contaminated clothing and wash it before reuse
 P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

EUH phrases : EUH208 - Contains Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert alkyl. May produce an allergic reaction

SOL-X EXTREME SYNTHETIC LUBE

Safety Data Sheet

according to Regulation (EC) No. 453/2010

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butane substance with national workplace exposure limit(s) (DK, GB, IE)	(CAS No) 106-97-8 (EC no) 203-448-7 (EC index no) 601-004-00-0	15 - 30	F+; R12	Flam. Gas 1, H220 Press. Gas
Hydrocarbons, C10-12, isoalkanes, <2% aromatics	(CAS No) 90622-57-4 (EC no) 923-037-2 (REACH-no) 01- 2119471991-29	5 - 15	Xn; R65 R66 R53	Asp. Tox. 1, H304 Aquatic Chronic 4, H413
propane substance with national workplace exposure limit(s) (DK, IE)	(CAS No) 74-98-6 (EC no) 200-827-9 (EC index no) 601-003-00-5	5 - 15	F+; R12	Flam. Gas 1, H220
Hydrocarbons, c&, n-alkanes, isoalkanes, cyclics	(CAS No) EC:927-510-4 (EC no) 927-510-4	5 - 15	F; R11 Xn; R65 Xi; R38 N; R51/53 R67	Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Hydrocarbons, C6, isoalkanes, <5% n- hexane	(CAS No) EC:931-254-9 (EC no) 931-254-9	1 - 5	F; R11 Xn; R65 N; R51/53 R67	Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Full text of R- and H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Get medical advice/attention if you feel unwell.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash with plenty of soap and water.
First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Do NOT induce vomiting. Rinse mouth. Drink plenty of water. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries Symptoms/injuries : Not expected to present a significant hazard under anticipated conditions of normal use.
after inhalation Symptoms/injuries : May cause respiratory irritation.
after skin contact Symptoms/injuries : Repeated exposure may cause skin dryness or cracking.
after eye contact Symptoms/injuries : Causes eye irritation.
after ingestion : May cause a light irritation of the linings of the mouth, throat, and gastrointestinal tract.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry powder. Foam.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol.
Explosion hazard : Explosion risk in case of fire.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources.

SOL-X EXTREME SYNTHETIC LUBE

Safety Data Sheet

according to Regulation (EC) No. 453/2010

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Use personal protective equipment as required.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use.

Precautions for safe handling : Do not spray on an open flame or other ignition source.

Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Does not require any specific or particular technical measures.

Storage conditions : Keep away from ignition sources. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Incompatible products : Oxidizing agent. Strong acids. Strong bases.

Incompatible materials : Direct sunlight. Heat sources. Sources of ignition.

Special rules on packaging : Keep only in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

propane (74-98-6)		
Denmark	Local name	Propan
Denmark	Grænseværdie (langvarig) (mg/m ³)	1800 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	1000 ppm
Ireland	Local name	Propane
Ireland	OEL (8 hours ref) (ppm)	1000 ppm
Ireland	Notes (IE)	Asphx
butane (106-97-8)		
Denmark	Local name	n-Butan
Denmark	Grænseværdie (langvarig) (mg/m ³)	1200 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	500 ppm
Ireland	Local name	Butane
Ireland	OEL (8 hours ref) (ppm)	1000 ppm
United Kingdom	Local name	Butane
United Kingdom	WEL TWA (mg/m ³)	1450 mg/m ³
United Kingdom	WEL TWA (ppm)	600 ppm
United Kingdom	WEL STEL (mg/m ³)	1810 mg/m ³
United Kingdom	WEL STEL (ppm)	750 ppm
United Kingdom	Remark (WEL)	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)

SOL-X EXTREME SYNTHETIC LUBE

Safety Data Sheet

according to Regulation (EC) No. 453/2010

8.2. Exposure controls

Materials for protective clothing	: Not required for normal conditions of use
Hand protection	: Protective gloves
Eye protection	: Not required for normal conditions of use
Skin and body protection	: Not required for normal conditions of use
Respiratory protection	: Not required for normal conditions of use



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: Colourless.
Odour	: odourless.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 0.72
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Direct sunlight. Heat. Open flame.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SOL-X EXTREME SYNTHETIC LUBE

Safety Data Sheet

according to Regulation (EC) No. 453/2010

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

CLEAR GREASE

Vaporizer	Aerosol
-----------	---------

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Do not pierce or burn, even after use.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR)	: 1950
UN-No. (IMDG)	: 1950
UN-No. (IATA)	: 1950

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: AEROSOLS
Proper Shipping Name (IMDG)	: AEROSOLS
Proper Shipping Name (IATA)	: AEROSOLS, FLAMMABLE
Transport document description (ADR)	: UN 1950 AEROSOLS, 2.1, (D)
Transport document description (IMDG)	: UN 1950 AEROSOLS, 2.1

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: 2.1
Danger labels (ADR)	: 2.1

SOL-X EXTREME SYNTHETIC LUBE

Safety Data Sheet

according to Regulation (EC) No. 453/2010



IMDG

Transport hazard class(es) (IMDG) : 2.1
Danger labels (IMDG) : 2.1



IATA

Transport hazard class(es) (IATA) : 2.1
Hazard labels (IATA) : 2.1



14.4. Packing group

Packing group (ADR) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : 5F
Special provisions (ADR) : 190, 327, 344, 625
Limited quantities (ADR) : 1L
Excepted quantities (ADR) : E0
Packing instructions (ADR) : P207, LP02
Special packing provisions (ADR) : PP87, RR6, L2
Mixed packing provisions (ADR) : MP9
Transport category (ADR) : 2
Special provisions for carriage - Packages (ADR) : V14
Special provisions for carriage - Loading, unloading and handling (ADR) : CV9, CV12
Special provisions for carriage - Operation (ADR) : S2
Tunnel restriction code (ADR) : D

- Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 959
Limited quantities (IMDG) : SP277
Excepted quantities (IMDG) : E0
Packing instructions (IMDG) : P207, LP02
Special packing provisions (IMDG) : PP87, L2

SOL-X EXTREME SYNTHETIC LUBE

Safety Data Sheet

according to Regulation (EC) No. 453/2010

EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U
Stowage category (IMDG) : None

- Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg
Special provisions (IATA) : A145, A167, A802
ERG code (IATA) : 10L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

IBC code : Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

Germany

VwVwS Annex reference : Water hazard class (WGK) 1, slightly hazardous to water (Classification according to VwVwS, Annex 4)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Denmark

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of R-, H- and EUH-phrases:

Aerosol 1	Aerosol, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Gas 1	Flammable gases, Category 1
Press. Gas	Gases under pressure
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H229	Pressurised container: May burst if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life
EUH208	Contains . May produce an allergic reaction

SOL-X EXTREME SYNTHETIC LUBE

Safety Data Sheet

according to Regulation (EC) No. 453/2010

SDS EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product