



SAFETY DATA SHEET

Foam Glass Cleaner

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Foam Glass Cleaner

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Glass cleaner.

1.3. Details of the supplier of the safety data sheet

Supplier Central Solutions (GB) Ltd
 Sol-X House
 Windmill Lane
 Doncaster
 DN6 9AT
 England
 Tel.: +44(0) 1302 708895
 email: info@solxsolutions.com www.solxsolutions.com

1.4. Emergency telephone number

Emergency telephone 01302 708 895

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

Health hazards Not Classified

Environmental hazards Not Classified

Human health Gas or vapour is harmful on prolonged exposure or in high concentrations. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

Environmental This product does not contain substances which are harmful to aquatic organisms or which may cause long term effects to the aquatic environment

Physicochemical Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

2.2. Label elements

Pictogram



Foam Glass Cleaner

| | |
|---------------------------------|--|
| Signal word | Danger |
| Hazard statements | H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated. |
| Precautionary statements | P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P102 Keep out of reach of children. P260 Do not breathe vapour/ spray. P271 Use only outdoors or in a well-ventilated area. P501 Dispose of contents/ container in accordance with local regulations. |
| Detergent labelling | < 5% aliphatic hydrocarbons, < 5% perfumes |

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| | | | |
|--|----------------------|---|-------------|
| 2-BUTOXYETHANOL | | | 1-5% |
| CAS number: 111-76-2 | EC number: 203-905-0 | REACH registration number: 01-2119475108-36 | |
| Classification | | | |
| Acute Tox. 4 - H302 | | | |
| Acute Tox. 4 - H312 | | | |
| Acute Tox. 4 - H332 | | | |
| Skin Irrit. 2 - H315 | | | |
| Eye Irrit. 2 - H319 | | | |
| PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS | | | 1-5% |
| CAS number: 68476-85-7 | EC number: 270-704-2 | | |
| Classification | | | |
| Flam. Gas 1 - H220 | | | |
| Press. Gas (Liq.) - H280 | | | |
| PROPAN-2-OL | | | 1-5% |
| CAS number: 67-63-0 | EC number: 200-661-7 | REACH registration number: 01-2119457558-25 | |
| Classification | | | |
| Flam. Liq. 2 - H225 | | | |
| Eye Irrit. 2 - H319 | | | |
| STOT SE 3 - H336 | | | |

Foam Glass Cleaner

| | |
|--|---|
| SODIUM NITRITE | <1% |
| CAS number: 7632-00-0 | EC number: 231-555-9 |
| | REACH registration number: 01-2119471836-27 |
| M factor (Acute) = 1 | |
| Classification | |
| Ox. Sol. 3 - H272 | |
| Acute Tox. 3 - H301 | |
| Eye Irrit. 2 - H319 | |
| Aquatic Acute 1 - H400 | |
| Hydrocarbons C11-C13 Isoalkanes, <2% aromatics | <1% |
| CAS number: 90622-58-5 | EC number: 920-901-0 |
| | REACH registration number: 01-2119456810-40 |
| Classification | |
| Asp. Tox. 1 - H304 | |

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|----------------------------|--|
| General information | Move affected person to fresh air at once. |
| Inhalation | If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately. |
| Ingestion | Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention. |
| Skin contact | Remove contaminated clothing immediately and wash skin with soap and water. |
| Eye contact | Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|----------------------------|---|
| General information | The severity of the symptoms described will vary dependent on the concentration and the length of exposure. |
|----------------------------|---|

4.3. Indication of any immediate medical attention and special treatment needed

| | |
|-----------------------------|------------------------|
| Notes for the doctor | Treat symptomatically. |
|-----------------------------|------------------------|

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|-------------------------------------|--|
| Suitable extinguishing media | Extinguish with foam, carbon dioxide, dry powder or water fog. |
|-------------------------------------|--|

5.2. Special hazards arising from the substance or mixture

| | |
|-------------------------|---|
| Specific hazards | Extremely flammable. Forms explosive mixtures with air. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Containers can burst violently or explode when heated, due to excessive pressure build-up. |
|-------------------------|---|

5.3. Advice for firefighters

Foam Glass Cleaner

Protective actions during firefighting Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours. Warn firefighters that aerosols are involved.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate. Avoid inhalation of vapours.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Do not spray on a naked flame or any incandescent material.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

2-BUTOXYETHANOL

Long-term exposure limit (8-hour TWA): WEL 25 ppm(Sk) 123 mg/m³

Short-term exposure limit (15-minute): WEL 50 ppm(Sk)

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

SODIUM NITRITE

Long-term exposure limit (8-hour TWA): No std.

Hydrocarbons C11-C13 Isoalkanes, <2% aromatics

Long-term exposure limit (8-hour TWA): SUP 177 ppm 1200 mg/m³

Foam Glass Cleaner

WEL = Workplace Exposure Limit

Ingredient comments

WEL = Workplace Exposure Limits

2-BUTOXYETHANOL (CAS: 111-76-2)

| | |
|-------------|--|
| DNEL | Workers - Dermal; Short term systemic effects: 44.5 mg/kg/day |
| | Workers - Inhalation; Short term systemic effects: 426 mg/m ³ |
| | Workers - Inhalation; Short term local effects: 123 mg/m ³ |
| | Workers - Dermal; Long term systemic effects: 38 mg/kg/day |
| | Workers - Inhalation; Long term systemic effects: 49 mg/kg/day |
| | Workers - Dermal; Long term systemic effects: 75 mg/kg/day |
| | Workers - Inhalation; Long term systemic effects: 20 ppm |
| | Workers - Dermal; Short term systemic effects: 89 mg/kg |
| | Workers - Inhalation; Short term systemic effects: 135 ppm |
| | Workers - Inhalation; Short term local effects: 50 ppm |
| | Workers - Inhalation; Short term systemic effects: 633 mg/m ³ |
| | Workers - Inhalation; Short term local effects: 246 mg/m ³ |
| | Workers - Inhalation; Long term systemic effects: 98 mg/m ³ |
| PNEC | Fresh water; 8.8 mg/l |
| | Marine water; 0.88 mg/l |
| | STP; 463 mg/l |
| | Sediment (Freshwater); 34.6 mg/kg |
| | Sediment (Marinewater); 3.46 mg/kg |
| | Soil; 2.8 mg/kg |

PROPAN-2-OL (CAS: 67-63-0)

| | |
|-------------|--|
| DNEL | Industry - Dermal; Long term systemic effects: 888 mg/kg/day |
| | Industry - Inhalation; Long term systemic effects: 500 mg/m ³ |
| | Consumer - Dermal; Long term systemic effects: 319 mg/kg/day |
| | Consumer - Dermal; Long term systemic effects: 26 mg/kg/day |
| | Consumer - Inhalation; Long term systemic effects: 89 mg/m ³ |
| PNEC | - Fresh water; 140.9 mg/l |
| | - Marine water; 140.9 mg/l |
| | - Intermittent release; 140.9 mg/l |
| | - Sediment (Freshwater); 552 mg/kg |
| | - Sediment (Marinewater); 552 mg/kg |
| | - STP; 2251 mg/l |
| | - Soil; 28 mg/kg |

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients.

Personal protection

When using do not smoke.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

Hand protection

Due to the packaging form, aerosol, risk of skin contact is small. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

Foam Glass Cleaner

| | |
|-------------------------------|--|
| Hygiene measures | Wash hands after handling. Wash promptly if skin becomes contaminated. Wash at the end of each work shift and before eating, smoking and using the toilet. Use appropriate skin cream to prevent drying of skin. |
| Respiratory protection | If ventilation is inadequate, suitable respiratory protection must be worn. |

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

| | |
|---|--|
| Appearance | Aerosol. |
| Colour | White. |
| Odour | Organic solvents. Lemon. |
| Initial boiling point and range | -40 to -2°C @ 1013 hPa |
| Flash point | <-40°C |
| Upper/lower flammability or explosive limits | Lower : 1.8% - Upper 9.5% |
| Vapour pressure | ca. 590 to 1760 kPa @ 45°C |
| Vapour density | ca. 1.5 at 15°C |
| Auto-ignition temperature | 410-580°C |
| Comments | Information given is applicable to the major ingredient. |

9.2. Other information

| | |
|----------------------------------|---|
| Other information | Not available. |
| Volatile organic compound | This product contains a maximum VOC content of 150 g/l. |

SECTION 10: Stability and reactivity

10.1. Reactivity

| | |
|-------------------|---|
| Reactivity | Stable at normal ambient temperatures and when used as recommended. |
|-------------------|---|

10.2. Chemical stability

| | |
|------------------|---|
| Stability | Avoid the following conditions: Heat, sparks, flames. |
|------------------|---|

10.3. Possibility of hazardous reactions

| | |
|---|---|
| Possibility of hazardous reactions | Does not decompose when used and stored as recommended. |
|---|---|

10.4. Conditions to avoid

| | |
|----------------------------|--|
| Conditions to avoid | Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight. |
|----------------------------|--|

10.5. Incompatible materials

| | |
|---------------------------|--|
| Materials to avoid | Keep away from oxidising materials, heat and flames. |
|---------------------------|--|

10.6. Hazardous decomposition products

| | |
|---|--|
| Hazardous decomposition products | Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours. |
|---|--|

SECTION 11: Toxicological information

Foam Glass Cleaner

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 16,329.9

Acute toxicity - dermal

ATE dermal (mg/kg) 21,632.65

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 224.49

| | |
|---|--|
| General information | Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal. |
| Inhalation | In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Unconsciousness, possibly death. |
| Skin contact | Skin irritation should not occur when used as recommended. Repeated exposure may cause skin dryness or cracking. |
| Eye contact | Vapour or spray in the eyes may cause irritation and smarting. |
| Acute and chronic health hazards | Arrhythmia (deviation from normal heart beat). In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. |
| Route of exposure | Inhalation |
| Target organs | Central nervous system Respiratory system, lungs |
| Medical symptoms | Arrhythmia (deviation from normal heart beat). Narcotic effect. Vapours may cause drowsiness and dizziness. |

Toxicological information on ingredients.

2-BUTOXYETHANOL

Toxicological effects Not available.

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 880.0

Species Rat

ATE oral (mg/kg) 880.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 1,060.0

Species Rabbit

ATE dermal (mg/kg) 1,060.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 450.0

Species Rat

Foam Glass Cleaner

| | |
|--|--|
| ATE inhalation (vapours mg/l) | 11.0 |
| Inhalation | No specific symptoms known. |
| Ingestion | Sore throat. |
| Skin contact | There may be mild irritation at the site of contact. |
| Eye contact | Irritation and redness, followed by blurred vision. |

PROPAN-2-OL

Acute toxicity - oral

**Acute toxicity oral
(LD₅₀ mg/kg)** 5,840.0

Species Rat

**Notes (oral LD₅₀) Acute
toxicity - dermal** Low order of acute toxicity.

**Acute toxicity dermal
(LD₅₀ mg/kg)** 16.4

Species Rabbit

Notes (dermal LD₅₀) Low order of acute toxicity.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) 6 hours. Not

Skin corrosion/irritation

Animal data irritating. Not

Respiratory sensitisation

Respiratory sensitisation available.

Germ cell mutagenicity

Genotoxicity - in vitro Negative.

Reproductive toxicity

**Reproductive toxicity
- fertility** No evidence of reproductive toxicity in animal studies.

Inhalation Drowsiness, dizziness, disorientation, vertigo.

Ingestion No specific health hazards known.

Skin contact No specific health hazards known.

Eye contact Irritating to eyes.

SODIUM NITRITE

Acute toxicity - oral

Foam Glass Cleaner

Acute toxicity oral (LD₅₀ mg/kg) 180.0

Species Rat

ATE oral (mg/kg) 180.0

AMMONIA ...%

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 350.0

Species Rat

BENZYL BENZOATE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 1,500.0

Species Rat

ATE oral (mg/kg) 1,500.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 4,000.0

Species Rat

ATE dermal (mg/kg) 4,000.0

6-acetyl-1,1,2,4,4,7-hexamethyltetraline

Acute toxicity - oral

ATE oral (mg/kg) 1,000.0

SECTION 12: Ecological Information

Ecotoxicity No negative effects on the aquatic environment are known. The product is not expected to be toxic to aquatic organisms.

Ecological information on ingredients.

2-BUTOXYETHANOL

Ecotoxicity No information available.

PROPAN-2-OL

Ecotoxicity The product is not expected to be hazardous to the environment.

12.1. Toxicity

Toxicity Not available.

Ecological information on ingredients.

2-BUTOXYETHANOL

Foam Glass Cleaner

| | |
|---|--|
| Toxicity | Not applicable. |
| <u>Acute aquatic toxicity</u> | |
| Acute toxicity - fish | LC ₅₀ , 96 hours: 1474 mg/l, Oncorhynchus mykiss (Rainbow trout) |
| Acute toxicity - aquatic invertebrates | EC ₅₀ , 48 hours: 1550 mg/l, Daphnia magna |
| Acute toxicity - aquatic plants | EC ₅₀ , 72 hours: 1840 mg/l, Pseudokirchneriella subcapitata LC ₅₀ , 72 hours: 500 mg/l, Freshwater algae |

PROPAN-2-OL

| | |
|---|---|
| Toxicity | Not available. |
| <u>Acute aquatic toxicity</u> | |
| Acute toxicity - fish | LC ₅₀ , 96 hours: 9640 mg/l, Pimephales promelas (Fat-head Minnow) |
| Acute toxicity - aquatic invertebrates | EC ₅₀ , : > 1000 mg/l, Daphnia magna 24 hours |
| Acute toxicity - aquatic plants | EC ₅₀ , 72 hours: > 1000 mg/l, Scenedesmus subspicatus |
| Acute toxicity - microorganisms | EC ₅₀ , : > 1000 mg/l, Activated sludge |

SODIUM NITRITE

| | |
|--------------------------------------|-------------------------------|
| <u>Acute aquatic toxicity</u> | |
| LE(C)₅₀ | 0.1 < L(E)C ₅₀ ≤ 1 |
| M factor (Acute) | 1 |

AMMONIA ...%

| | |
|--------------------------------------|-------------------------------|
| <u>Acute aquatic toxicity</u> | |
| LE(C)₅₀ | 0.1 < L(E)C ₅₀ ≤ 1 |

(L) d-para-mentha-1,8-diene

| | |
|--|-------------------------------|
| <u>Acute aquatic toxicity</u> | |
| LE(C)₅₀ | 0.1 < L(E)C ₅₀ ≤ 1 |
| M factor (Acute) | 1 |
| <u>Chronic aquatic toxicity</u> | |
| M factor (Chronic) | 1 |

BENZYL BENZOATE

| | |
|--------------------------------------|-------------------------------|
| <u>Acute aquatic toxicity</u> | |
| LE(C)₅₀ | 0.1 < L(E)C ₅₀ ≤ 1 |
| M factor (Acute) | 1 |

6-acetyl-1,1,2,4,4,7-hexamethyltetraline

| | |
|--------------------------------------|--|
| <u>Acute aquatic toxicity</u> | |
|--------------------------------------|--|

Foam Glass Cleaner

| | |
|---------------------------------|-------------------|
| LE(C) ₅₀ | 0.1 < L(E)C50 ≤ 1 |
| M factor (Acute) | 1 |
| <u>Chronic aquatic toxicity</u> | |
| M factor (Chronic) | 1 |

LIMONENE

| | |
|---------------------------------|-------------------|
| Toxicity | Not available. |
| <u>Acute aquatic toxicity</u> | |
| LE(C) ₅₀ | 0.1 < L(E)C50 ≤ 1 |
| M factor (Acute) | 1 |
| <u>Chronic aquatic toxicity</u> | |
| M factor (Chronic) | 1 |

d-alpha-Pinene

| | |
|---------------------------------|-------------------|
| <u>Acute aquatic toxicity</u> | |
| LE(C) ₅₀ | 0.1 < L(E)C50 ≤ 1 |
| M factor (Acute) | 1 |
| <u>Chronic aquatic toxicity</u> | |
| M factor (Chronic) | 1 |

12.2. Persistence and degradability

Persistence and degradability Not available.

Ecological information on ingredients.

2-BUTOXYETHANOL

| | |
|--------------------------------------|------------------------------------|
| Persistence and degradability | The product is biodegradable. |
| Biodegradation | Water - Degradation 90.4%: 28 days |

PROPAN-2-OL

| | |
|--------------------------------------|--|
| Persistence and degradability | Not available. |
| Biodegradation | Degradation (%) - Degradation (%) 95: 21 days |

LIMONENE

| | |
|--------------------------------------|----------------|
| Persistence and degradability | Not available. |
|--------------------------------------|----------------|

12.3. Bioaccumulative potential

Bioaccumulative potential Not available.

Ecological information on ingredients.

Foam Glass Cleaner

2-BUTOXYETHANOL

Bioaccumulative potential The product is not bioaccumulating.
Partition coefficient log Pow: 0.81 at 25°C

PROPAN-2-OL

Bioaccumulative potential Not available.
Partition coefficient log Pow: 0.05

LIMONENE

Bioaccumulative potential Not available.

12.4. Mobility in soil

Mobility Not known.

Ecological information on ingredients.

2-BUTOXYETHANOL

Mobility Readily absorbed into soil.
Surface tension 65.03 mN/m @ 20°C

PROPAN-2-OL

Mobility Not known.
Adsorption/desorption coefficient Water - Koc: ~ 1.1 @ °C
Henry's law constant 0.00000338 atm m³/mol @ 25°C

LIMONENE

Mobility Not known.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment Not available.

Ecological information on ingredients.

2-BUTOXYETHANOL

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

PROPAN-2-OL

Results of PBT and vPvB assessment Not available.

LIMONENE

Foam Glass Cleaner

Results of PBT and vPvB assessment Not available.

12.6. Other adverse effects

Other adverse effects Not available.

Ecological information on ingredients.

2-BUTOXYETHANOL

Other adverse effects Negligible ecotoxicity.

PROPAN-2-OL

Other adverse effects Not available.

LIMONENE

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Do not puncture or incinerate, even when empty.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Empty containers must not be punctured or incinerated because of the risk of an explosion.

SECTION 14: Transport information

General This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities. Aerosols not so packed and labelled must show the following.

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID label 2.1

Foam Glass Cleaner

IMDG class 2.1

ICAO class/division 2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-D, S-U

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Control of Substances Hazardous to Health Regulations 2002 (as amended).
EH40/2005 Workplace exposure limits.
The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).
The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].

EU legislation Commission Regulation (EU) No 453/2010 of 20 May 2010.

Guidance Workplace Exposure Limits EH40.
Safety Data Sheets for Substances and Preparations.
Approved Classification and Labelling Guide (Sixth edition) L131.
British Aerosol Manufacturers Code of Practice 7th. Edition 1999

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments Supplemental information added.

Revision date 15/02/2018

Revision 3

SDS number 11705

SDS status Approved.

Foam Glass Cleaner

Hazard statements in full

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H229 Pressurised container: may burst if heated.
H272 May intensify fire; oxidiser.
H280 Contains gas under pressure; may explode if heated.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.