

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/6

Traffic Film Remover

Revision 9
Revision date 2017-10-05

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	TFR
REACH	ALL INGREDIENTS IN THIS FORMULATION HAVE BEEN REGISTERED (WHERE REQUIRED) FOR APPLICABLE USES.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Description	Aqueous solution.
-------------	-------------------

1.3. Details of the supplier of the safety data sheet

Company	Central Solutions (GB) Ltd
Address	Sol-X House Windmill Lane Norton Doncaster DN6 9AT
Web	www.solxsolutions.com
Telephone	+44 (0)1302 708895
Fax	+44 (0)1302 708895
Email	info@solxsolutions.com
Email address of the competent person	info@solxsolutions.com

1.4. Emergency telephone number


Emergency telephone number	01302 708895
Company	Central Solutions (GB) Ltd 24hrs

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	Xi; R36/38 Symbols: Xi: Irritant.
Main hazards	Irritating to eyes and skin.
2.1.2. Classification - EC 1272/2008	Skin Corr. 1A: H314;

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Skin Corr. 1A: H314 - Causes severe skin burns and eye damage.

Traffic Film Remover

Revision 9

Revision date 2017-10-05

2.2. Label elements

Precautionary Statement: Prevention	P102 - Keep out of reach of children. P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P264 - Wash hands thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P301+P312 - IF SWALLOWED: Call a POISON CENTER/doctor/ /if you feel unwell. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P363 - Wash contaminated clothing before reuse.
Precautionary Statement: Storage	P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to rEQUIREMENTS OF LOCAL AUTHORITIES

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
WATER					80 - 90%		
trisodium nitrilotriacetate	607-620-00-6	5064-31-3	225-768-6		1 - 10%	Carc. Cat. 3; R40 Xn; R22 Xi; R36	
LAURYL BETAINE		66455-29-6	266-368-1		0 - 0.5%	Xi; R38-41	
D-Glucopyranose, Oligomeric, Decyl, Octyl, Glycoside					0 - 0.5%	Xi; R41	
1-Propanaminium, 3 Amino-N(carboxymethyl)N,N.Dimethyl N Coco acyl dervis inner salts					0 - 0.5%	Xi; R36	
Ethylene glycol monobutyl ether (2-Butoxyethanol)	603-014-00-0	111-76-2	203-905-0		0 - 0.5%	Xn; R20/21/22 Xi; R36/38	
Sodium hydroxide	011-002-00-61310-73-2		215-185-5	01-2119457892-27	1 - 10%	C; R35	
SODIUM METASILICATE PENTA HYDRATE		6834-92-0	229-912-9	01-2119449811-37 01-2119449811-37	1 - 10%	C; R34	
ALCOHOL ETHOXYLATE		68439-46-3			1 - 10%	Xn; R22 Xi; R41	
TETRA POTASSIUM PYROPHOSPHATE		7320-34-5	230-785-7	01-2119489369-18	0.5 - 1%	Xi; R36	
Mono ethylene glycol (Ethane-1,2-diol particulate)	603-027-00-1	107-21-1	203-473-3		0 - 0.5%	Xn; R22	
DYE					0 - 0.5%		

Traffic Film Remover

Revision 9

Revision date 2017-10-05

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
WATER					80 - 90%		
trisodium nitrilotriacetate	607-620-00-6	5064-31-3	225-768-6		1 - 10%	Carc. 2: H351; Acute Tox. 4: H302; Eye Irrit. 2: H319;	
LAURYL BETAINE		66455-29-6	266-368-1		0 - 0.5%	Eye Dam. 1: H318; Aquatic Chronic 3: H412;	
D-Glucopyranose, Oligomeric, Decyl, Octyl, Glycoside					0 - 0.5%	Eye Dam. 1: H318;	
1-Propanaminium, 3 Amino-N(carboxymethyl)N,N.Dimethyl N Coco acyl dervis inner salts					0 - 0.5%	Skin Irrit. 2: H315;	
Ethylene glycol monobutyl ether (2-Butoxyethanol)	603-014-00-0	111-76-2	203-905-0		0 - 0.5%	Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315;	
Sodium hydroxide	011-002-00-61310-73-2		215-185-5	01-2119457892-27	1 - 10%	Skin Corr. 1A: H314;	
SODIUM METASILICATE PENTA HYDRATE		6834-92-0	229-912-9	01-2119449811-37 01-2119449811-37	1 - 10%	Met. Corr. 1: H290; Skin Corr. 1B: H314; Eye Dam. 1: H318; STOT SE 3: H335;	
ALCOHOL ETHOXYLATE		68439-46-3			1 - 10%	Acute Tox. 4: H302; Eye Dam. 1: H318;	
TETRA POTASSIUM PYROPHOSPHATE		7320-34-5	230-785-7	01-2119489369-18	0.5 - 1%	Eye Irrit. 2: H319;	
Mono ethylene glycol (Ethane-1,2-diol particulate)	603-027-00-1	107-21-1	203-473-3		0 - 0.5%	Acute Tox. 4: H302;	
DYE					0 - 0.5%		

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention. May cause irritation to respiratory system.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Carbon dioxide (CO ₂).
--	------------------------------------

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Wear suitable protective equipment.
--	-------------------------------------

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

Traffic Film Remover

Revision 9

Revision date 2017-10-05

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Ethylene glycol monobutyl ether (2-Butoxyethanol)	WEL 8-hr limit ppm: 25 WEL 15 min limit ppm: 50 WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 123 WEL 15 min limit mg/m3: 101.2 WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
Mono ethylene glycol (Ethane-1,2-diol particulate)	WEL 8-hr limit ppm: - WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 10 WEL 15 min limit mg/m3: - WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
Mono ethylene glycol (Ethane-1,2-diol vapour)	WEL 8-hr limit ppm: 20 WEL 15 min limit ppm: 40 WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 52 WEL 15 min limit mg/m3: 104 WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
Sodium hydroxide	WEL 8-hr limit ppm: - WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: - WEL 15 min limit mg/m3: 2 WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:

DNEL: Derived no-effect level.

No data is available on this product.

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Not normally required.
8.2.2. Individual protection measures	Wear suitable protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Not normally required.

Traffic Film Remover

Revision 9

Revision date 2017-10-05

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Green
Odour	Characteristic
pH	13.5 NOMINAL
Initial boiling point	100
Relative density	1.06 NOMINAL

Water solubility

Slightly soluble in water.

SECTION 10: Stability and reactivity

10.2. Chemical stability

Stable under normal conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin corrosion/irritation	Irritating to eyes and skin. May cause degreasing of the skin. Risk of serious damage to eyes.
---------------------------	--

SECTION 12: Ecological information

12.2. Persistence and degradability

	Inorganic materials are inherently not biodegradable however those present in this formulation/product are either of no known significant environmental hazard or are readily neutralised to form inert salts.
--	--

12.3. Bioaccumulative potential

No data is available on this product.

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

SECTION 14: Transport information

Further information

	The product is not classified as dangerous for carriage.
--	--

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations	COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC. REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.
-------------	--

15.2. Chemical safety assessment

Traffic Film Remover

Revision 9

Revision date 2017-10-05

15.2. Chemical safety assessment

No chemical Safety assessment has been carried out by the supplier.

SECTION 16: Other information

Other information

Revision	<p>This document differs from the previous version in the following areas:</p> <ul style="list-style-type: none"> 1 - Description. 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Response. 8 - 8.2.2. Individual protection measures. 8 - DNEL: Derived no-effect level. 11 - Skin corrosion/irritation. 12 - 12.3. Bioaccumulative potential. 15 - Regulations.
Text of risk phrases in Section 3	<p>R20/21/22 - Harmful by inhalation, in contact with skin and if swallowed. R22 - Harmful if swallowed. R34 - Causes burns. R35 - Causes severe burns. R36/38 - Irritating to eyes and skin. R36 - Irritating to eyes. R38 - Irritating to skin. R40 - Limited evidence of a carcinogenic effect. R41 - Risk of serious damage to eyes.</p>
Text of Hazard Statements in Section 3	<p>Acute Tox. 4: H302 - Harmful if swallowed. Eye Irrit. 2: H319 - Causes serious eye irritation. Carc. 2: H351 - Suspected of causing cancer . Eye Dam. 1: H318 - Causes serious eye damage. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Skin Irrit. 2: H315 - Causes skin irritation. Acute Tox. 4: H312 - Harmful in contact with skin. Acute Tox. 4: H332 - Harmful if inhaled. Skin Corr. 1A: H314 - Causes severe skin burns and eye damage. Skin Corr. 1B: H314 - Causes severe skin burns and eye damage. Met. Corr. 1: H290 - May be corrosive to metals. STOT SE 3: H335 - May cause respiratory irritation.</p>

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.