



SAFETY DATA SHEET

Liquid Gasket

Page: 1

Compilation date: 05/08/2013

Revision date: 20/10/2016

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: Liquid Gasket

Product code: SXLG50

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: Central Solutions (GB) Ltd

Sol-X House

Windmill Lane

Norton

Doncaster

DN6 9AT

England

Tel: +44(0)1302 708895

Fax: +44(0)1302 708895

Email: info@solxsolutions.com

1.4. Emergency telephone number

Emergency tel: CHEMTEL Tel: 813-248-0573 (International)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Sens. 1: H317; Eye Irrit. 2: H319; -: EUH208

Most important adverse effects: Contains 1-acetyl-2-phenyl hydrazine and maleic acid. May produce an allergic reaction.
May cause an allergic skin reaction. Causes serious eye irritation.

2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains 1-acetyl-2-phenyl hydrazine and maleic acid. May produce an allergic reaction.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

Hazard pictograms: GHS07: Exclamation mark



[cont...]

SAFETY DATA SHEET

Liquid Gasket

Page: 2

Signal words: Warning

Precautionary statements: P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+350: IF ON SKIN: Gently wash with plenty of soap and water.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+313: If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

MONO-2-METHACRYLOYL OXYETHYL HYDROGEN SUCCINATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
244-096-4	20882-04-6	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Sens. 1: H317	5-10%

2-HYDROXYETHYL METHACRYLATE - REACH registered number(s): 01-2119490169-29-0000

212-782-2	868-77-9	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317	1-5%
-----------	----------	---	--	------

AMORPHOUS SILICA

231-545-4	7631-86-9	Substance with a Community workplace exposure limit.	-	1-5%
-----------	-----------	---	---	------

ETHYLENE GLYCOL

203-473-3	107-21-1	-	Acute Tox. 4: H302	1-5%
-----------	----------	---	--------------------	------

CUMENE HYDROPEROXIDE

201-254-7	80-15-9	-	Org. Perox. EF: H242; Acute Tox. 3: H331; Acute Tox. 4: H312; Acute Tox. 4: H302; STOT RE 2: H373; Skin Corr. 1B: H314	<1%
-----------	---------	---	---	-----

1-ACETYL-2-PHENYL HYDRAZINE

204-055-3	114-83-0	-	Acute Tox. 3: H301; Skin Irrit. 2: H315; STOT SE 3: H335; Eye Irrit. 2: H319; Skin Sens. 1: H317	<1%
-----------	----------	---	--	-----

[cont...]

SAFETY DATA SHEET

Liquid Gasket

Page: 3

MALEIC ACID

203-742-5	110-16-7	-	Acute Tox. 4: H302; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Skin Sens. 1: H317	<1%
-----------	----------	---	--	-----

P-BENZOQUINONE

203-405-2	106-51-4	-	Acute Tox. 3: H331; Acute Tox. 3: H301; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Aquatic Acute 1: H400	<1%
-----------	----------	---	---	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: Exposure may cause coughing or wheezing.

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

[cont...]

SAFETY DATA SHEET

Liquid Gasket

Page: 4

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS.
Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): PC1: Adhesives, sealants.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

AMORPHOUS SILICA

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	-	2.4 mg/m ³	-

ETHYLENE GLYCOL

UK	52mg/m ³	104mg/m ³	-	-
----	---------------------	----------------------	---	---

P-BENZOQUINONE

UK	0.1	0.3	-	-
----	-----	-----	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

[cont...]

SAFETY DATA SHEET

Liquid Gasket

Page: 5

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Orange

Odour: Sweet-smelling

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: No data available.

Viscosity: Viscous

Melting point/range°C: No data available.

upper: No data available.

Autoflammability°C: No data available.

Relative density: 0.997

Flammability limits %: lower: No data available.

Part.coeff. n-octanol/water: No data available.

Vapour pressure: No data available.

VOC g/l: 35

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

[cont...]

SAFETY DATA SHEET

Liquid Gasket

Page: 6

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

2-HYDROXYETHYL METHACRYLATE

DERMAL	RBT	LD50	>3000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg

AMORPHOUS SILICA

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>1000	mg/kg

ETHYLENE GLYCOL

DERMAL	RBT	LD50	10626	mg/kg
ORAL	RAT	LD50	4700	mg/kg
VAPOURS	RAT	6H LC50	>2.5	mg/l

CUMENE HYDROPEROXIDE

ORL	MUS	LDLO	5	gm/kg
ORL	RAT	LD50	382	mg/kg
SCU	RAT	LD50	382	mg/kg

1-ACETYL-2-PHENYL HYDRAZINE

ORAL	MUS	LD50	270	mg/kg
------	-----	------	-----	-------

MALEIC ACID

DERMAL	RBT	LD50	1560	mg/kg
ORAL	RAT	LD50	708	mg/kg
VAPOURS	RBT	1H LC50	>720	mg/m3

P-BENZOQUINONE

ORAL	MUS	LD50	130	mg/kg
ORAL	MUS	LDLo	100	mg/kg
ORAL	RAT	LD50	25	mg/kg

[cont...]

SAFETY DATA SHEET

Liquid Gasket

Page: 7

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: Exposure may cause coughing or wheezing.

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

2-HYDROXYETHYL METHACRYLATE

DAPHNIA MAGNA	48H EC50	380	mg/l
GREEN ALGA (<i>Selenastrum capricornutum</i>)	72H EC50	836	mg/l
ORYZLAS LATIPES	96H LC50	>100	mg/l
PSEUDOMONAS FLUORESCENS	16H EC50	>3000	mg/l

ETHYLENE GLYCOL

DAPHNIA MAGNA	48H LC50	41000	mg/l
GOLDEN ORFE (<i>Leuciscus idus</i>)	48H LC50	10000	mg/l
RAINBOW TROUT (<i>Oncorhynchus mykiss</i>)	96H LC50	18500	mg/l

MALEIC ACID

DAPHNIA MAGNA	48H EC50	42.81	mg/l
FATHEAD MINNOW (<i>Pimephales promelas</i>)	96H LC50	5	mg/l
<i>Pseudokirchnerella subcapitata</i>	72H EC50	74.35	mg/l

P-BENZOQUINONE

PIMEPHALES PROMELAS	96H LC50	0.045	mg/l
---------------------	----------	-------	------

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

[cont...]

SAFETY DATA SHEET

Liquid Gasket

Page: 8

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

AFKORTINGEN

ORL - Oraal

DRM - Dermale

INH - Inhalatie

MUS - Muis RBT

- Konijn

OPT - Beschouw dispense

SCU - Onderhuids

PBT - Duurzame bio-accumulerend zijn giftige

VOC - Vluchtige organische stof

STP - Afvalwaterzuiveringsinstallatie

[cont...]

SAFETY DATA SHEET

Liquid Gasket

Page: 9

LC50 - Letale Concentratie 50%

LD50 - Letale dosis 50%

PNEC - Voorspelde no effect concentration

DNEL - Afgeleide no effect level

Phrases used in s.2 and s.3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H242: Heating may cause a fire.

H301: Toxic if swallowed.

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H335: May cause respiratory irritation.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H400: Very toxic to aquatic life.

Legal disclaimer: This company shall not be held liable for any damage resulting from handling or from contact with the above product.